Tanium Engage User Guide

2026H2 Semiannual Release

Version 1.16

November 17, 2026



The information in this document is subject to change without notice. Further, the information provided in this document is provided "as is" and is believed to be accurate, but is presented without any warranty of any kind, express or implied, except as provided in Tanium's customer sales terms and conditions. Unless so otherwise provided, Tanium assumes no liability whatsoever, and in no event shall Tanium or its suppliers be liable for any indirect, special, consequential, or incidental damages, including without limitation, lost profits or loss or damage to data arising out of the use or inability to use this document, even if Tanium Inc. has been advised of the possibility of such damages.

Any IP addresses used in this document are not intended to be actual addresses. Any examples, command display output, network topology diagrams, and other figures included in this document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

Please visit https://help.tanium.com for the most current Tanium product documentation.

This documentation may provide access to or information about content, products (including hardware and software), and servicesprovided by third parties ("Third Party Items"). With respect to such Third Party Items, Tanium Inc. and its affiliates (i) are not responsible for such items, and expressly disclaim all warranties and liability of any kind related to such Third Party Items and (ii) will not be responsible for any loss, costs, or damages incurred due to your access to or use of such Third Party Items unless expressly set forth otherwise in an applicable agreement between you and Tanium.

Further, this documentation does not require or contemplate the use of or combination with Tanium products with any particular Third Party Items and neither Tanium nor its affiliates shall have any responsibility for any infringement of intellectual property rights caused by any such combination. You, and not Tanium, are responsible for determining that any combination of Third Party Items with Tanium products is appropriate and will not cause infringement of any third party intellectual property rights.

Tanium is committed to the highest accessibility standards for our products. To date, Tanium has focused on compliance with U.S.Federal regulations - specifically Section 508 of the Rehabilitation Act of 1998. Tanium has conducted 3rd party accessibility assessments over the course of product development for many years. We certify against the WCAG 2.2 / VPAT 2.5 standards for all major product modules. Tanium performs ongoing reassessments as appropriate, given the scope and type of changes to the UI and product features from release to release. In the most recent testing, the Tanium Console UI achieved supports or partially supports for all applicable WCAG 2.2 criteria. Tanium can make available any VPAT reports on a module-by-module basis as part of a larger solution planning process for any customer or prospect.

As new products and features are continuously delivered, Tanium will conduct testing to identify potential gaps in compliance with accessibility guidelines. Tanium is committed to making commercially reasonable efforts to address any gaps as quickly as is feasible, given the severity of the issue and scope of the changes. Tanium factors these objectives into the ongoing delivery schedule of features and releases with our existing resources.

Tanium welcomes customer input on making solutions accessible based on your Tanium modules and assistive technology requirements. Accessibility requirements are important to the Tanium customer community and we are

©2026 Tanium Inc. All Rights Reserved

committed to prioritizing these compliance efforts as part of our overall product roadmap. Tanium maintains transparency on our progress and milestones and welcomes any further questions or discussion around this work. Contact your sales representative, Tanium Support atsupport@tanium.com, or email accessibility@tanium.com to make further inquiries.

Tanium is a trademark of Tanium, Inc. in the U.S. and other countries. Third-party trademarks mentioned are the property of the irrespective owners.

Kubernetes®, K8s®, and the Kubernetes logo are registered trademarks of The Linux Foundation®.

Android, ChromeOS, and Google are trademarks of Google LLC.

iOS, iPad, iPadOS, iPhone, Mac, and macOS are trademarks of Apple Inc., and registered in the U.S. and other countries and regions.

Patents: https://www.tanium.com/patents

Tanium Open Source Disclosure : https://tanium.github.io/opensource/

© 2026 Tanium Inc. All rights reserved.

Table of contents

Overview 7
- Surveys 7
- Notifications 8
- Targeting 8
- Remediations 8
- Supported languages 10
- Interoperability with other Tanium products 10

Requirements 12
- Core platform dependencies 12
- Computer group dependencies 12
- Solution dependencies 12
  - Tanium recommended installation 13
  - Import specific solutions 13
  - Required dependencies 13
  - Feature-specific dependencies 13
- Client extensions and endpoint tools 14
- Tanium™ Module Server 14
- Endpoints 14
  - Supported operating systems 14
- Host and network security requirements 15
  - Ports 15
  - Security exclusions 15
    - Engage endpoint exclusions 16
    - Engage server exclusions 16
- User role requirements 16

Getting started with Engage 20

Installing 22

©2026 Tanium Inc. All Rights Reserved

Before you begin 22
Import Engage with default settings 22
Default settings for Engage 23
Import Engage with custom settings 23
Upgrade Engage 23
Verify Engage version 24
Troubleshoot issues 24

Configuring 25
Install and configure Tanium Endpoint Configuration 25
Manage solution configurations with Tanium Endpoint Configuration 25
Install and configure Tanium End-User Notifications 27
Configure Engage 27
Configure the Engage action group 27
Organize computer groups 28
Set up Engage users 28

Creating surveys 31
Create survey 31
Schedule survey run 35
View existing survey status 36
End user survey experience 36
View survey results 37
View survey responses for a single endpoint 38
Run survey again 38
Create question templates 39
Export and import surveys 40
Export survey 40
Import survey 40
Clone survey 40

Understanding employee sentiment 42
Overall employee sentiment score 42
Scope performance and sentiment scores 42
Review metric summary 43
Overall Response Rate 44
Employee Response 44

©2026 Tanium Inc. All Rights Reserved

Total Responses by Sentiment 44
Employee Sentiment Score 44
Endpoint Performance Score 44
DEX Scores Over Time 44
View digital employee experience (DEX) on a single endpoint 44

Creating remediation tasks 46
Default remediation tasks 46
Create remediation package 47
Tanium packages 47
Custom package 47
Create remediation task 47
Sample: (Windows with PowerShell Script and Notepad) Create remediation package that runs as user 48
Sample: (Windows with PowerShell Script) Create remediation package that runs as user 52
Sample: (macOS with Shell Script and TXT File) Create remediation package that runs as user 56
Sample: (macOS with Shell Script) Create remediation package that runs as user 58

Creating notifications 63
Create a theme 63
Create notification 65
Schedule notification run 68
Clone notification 69
View existing notification status 69
Delete notification 70
Export and import notifications 70
Export notification 70
Import notification 71

Troubleshooting 72
Collect logs 72
Collect troubleshooting package for Engage 72
Collect troubleshooting information from endpoints 72
Verify endpoint tools 73
Contact Tanium Support 74

©2026 Tanium Inc. All Rights Reserved

Engage overview

With Engage, you can create surveys to collect qualitative feedback from endpoint users, send notifications to targeted endpoints managed using Tanium™ Client, and deploy remediations to these endpoints to correct problems.

Surveys

A survey in Engage is a set of up to five questions that you want to send to a defined set of endpoints. Surveys are sent to all users of an endpoint and appear on the endpoint as a Tanium end-user notification. If the user postpones the survey, they can reopen the survey in the self-service portal.

The questions in a survey can be unique to that survey, or you can copy questions from template questions that you can create.

Answer types

Multiple choice: A question that provides up to 10 answers from which the user can select one answer.

Sentiment: A question that collects data about the user's feelings. The user responses to sentiment questions contribute to the employee sentiment score.

The sentiment score is calculated on a 1-5 Likert scale rating about the user's feelings (5: Strong Positive, 1: Strong Negative). The overall sentiment score is a scaled average of all sentiment score questions across all surveys that have sentiment questions, and gets a rating based on the following calculations:

- Strong Positive: 87.5-100
- Positive: 62.5-87.4
- Neutral: 37.5-62.4
- Negative: 12.5-37.4

©2026 Tanium Inc. All Rights Reserved

- Strong Negative: 0-12.4

Notifications

A notification in Engage is information that only requires acknowledgment that you want to send to a defined set of endpoints. Notifications are sent to all users of an endpoint and appear on the endpoint as a Tanium™ End-User Notifications notification message. Use notifications to notify employees of operational and service issues; send notifications to retrieve IT-related details from employees and avoid excess service tickets. You can also send notifications to communicate announcements about training, policy updates, and organizational changes.

Targeting

To configure which endpoints receive a survey or notification, you must configure targeting.

The targeting for a survey or notification is a computer group, which is a set of endpoints that you want to manage together. You might have existing computer groups to target surveys or notifications, or you might want to create new computer groups.

The user that creates the survey or notification must have management rights to this computer group. For more information about assigning computer groups to a user, see Tanium Platform User Guide: Manage computer group assignments for a user.

For each survey or notification, you can optionally configure trigger conditions that define sensor or metric thresholds that must be met to show the survey or notification on a targeted endpoint. When you publish a survey, the survey runs in the background on each targeted endpoint. However, the end users of the endpoint do not see the survey until the trigger conditions for the survey are met. Similarly, when you schedule a notification, the end users of the endpoint do not see the notification until the trigger conditions for the notification are met. If you do not specify trigger conditions in the survey or notification, the survey or notification appears to end users on all targeted endpoints.

Remediations

You can configure one remediation per survey or notification. A remediation can open a link or deploy an action to the targeted endpoint.

- For surveys, a remediation is attached to a question answer in the last question of the survey.

©2026 Tanium Inc. All Rights Reserved

Multiple choice questions can have a package or link remediation. Sentiment questions can contain only a link remediation.

- For notifications, the remediation action begins when the user clicks a button to acknowledge the notification.

Package remediations are packages that a user can choose to deploy to their endpoint to solve the issue that was found with trigger conditions. For example, the trigger condition might be a missing patch that sends a survey question to the endpoint user. If the user chooses to install the patch, the remediation package is deployed to the endpoint. In another scenario, a user might experience multiple system crashes, and get sent a survey that asks them if they want to open an IT ticket, which opens a URL to their internal support site.

You can choose from the default remediation tasks or create your own tasks. For more information, see Creating remediation tasks on page 46.

Default remediation tasks

Restart Endpoint

Restarts the target device.

Clear Microsoft Teams Cache

Clears cache to resolve problems with Microsoft Teams.

Clear DNS Cache

Clears DNS cache to help resolve network issues.

Enable / Disable Fast Start

Enables or disables the Windows OS Fast Start feature.

Restart <application>

Restarts the (macOS) Apple Safari, Cisco Webex, Google Chrome, Microsoft Edge, Microsoft Outlook, Microsoft Teams, Mozilla Firefox, Slack, or Zoom application.

User Disk Cleanup

Performs light (Recycle bin empty) clean.

©2026 Tanium Inc. All Rights Reserved

Supported languages

You can select one of the languages in the following table for user interface (UI) text in the Engage workbench and Tanium documentation.

The language that you select for the workbench also sets the date and time format:

- Dates: In the table, the letters `dd`, `mm`, and `yyyy` represent the digits for day, month, and year respectively.
- Times: English (United States) times use the 12-hour clock in the format hh:mm:ss [AM|PM] <time zone>, where `hh`, `mm`, and `ss` represent the hour, minute, and second respectively. Other times use the 24-hour clock, where GMT-<#> indicates the offset from Greenwich Mean Time (GMT). For example, `GMT-7` indicates a time zone that is 7 hours ahead of GMT.

Supported languages with associated date and time formats

Language	Locale code	Date and time format
English (United States)	en-US	mm/dd/yyyy [AM|PM] <time zone>
French (France)	fr-FR	dd/mm/yyyy GMT- <#>
German (Germany)	de-DE	dd/mm/yyyy GMT- <#>
Japanese (Japan)	ja-JP	yyyy/mm/dd GMT- <#>
Korean (Korea, Republic of)	ko-KR	yyyy.mm.dd GMT- <#>
Spanish (Latin American)	es-LA	dd/mm/yyyy GMT- <#>

For information about language support, which types of text are translated, and the steps to select a language, see Tanium Console User Guide: Reference: Language support.

Interoperability with other Tanium products

Engage works with other Tanium products.

Directory Query

Engage uses Tanium™ Directory Query to collect user attributes for survey results. For more information, see Tanium Directory Query.

End-User Notifications

Engage uses Tanium End-User Notifications to notify users about surveys and notifications. For more

©2026 Tanium Inc. All Rights Reserved

information, see Install and configure Tanium End-User Notifications on page 27.

Endpoint Configuration

Engage uses Tanium™ Endpoint Configuration to deploy remediation tasks to endpoints. For more information, see Install and configure Tanium Endpoint Configuration on page 25.

Performance

Engage uses Tanium™ Performance for metrics to monitor, measure and improve the performance of end user digital experiences. For more information, see Tanium Performance.

Reporting

Engage uses Tanium™ Reporting to create the charts on the **Engage Overview** page. For more information, see Tanium Reporting.

©2026 Tanium Inc. All Rights Reserved

Engage requirements

Review the requirements before you install and use Engage.

Core platform dependencies

Make sure that your environment meets the following requirements:

- Tanium license that includes Engage. For more information about how to get Engage, see Tanium Solutions & Bundles.
- Tanium™ Core Platform servers
- Any supported version of Tanium Client. For more information, see Client version and host system requirements. If you use a Client version that is not listed, certain product features might not be available, or stability issues can occur that can only be resolved by upgrading to one of the listed Client versions.

Computer group dependencies

When you first sign in to Tanium Console after a fresh installation of Tanium Server, the server automatically imports the `All Windows` and `All Macs` computer groups.

Solution dependencies

Other Tanium solutions are required for Engage to function (required dependencies) or for specific Engage features to work (feature-specific dependencies). The installation method that you select determines if the Tanium Server automatically imports dependencies or if you must manually import them.

©2026 Tanium Inc. All Rights Reserved

Note: Some Engage dependencies have their own dependencies, which you can see in the lists of required and feature-specific dependencies below. Where a dependency links to its own user guide, that link opens the guide for the latest version of the solution, not necessarily the minimum version that Engage requires.

Tanium recommended installation

If you select **Tanium Recommended Installation** when you import Engage, the Tanium Server automatically imports all your licensed solutions at the same time. For more information, see Tanium Console User Guide: Import all modules and services.

Import specific solutions

If you select only Engage to import, the Tanium Server automatically imports the latest available versions of any required dependencies that are missing. If some required dependencies are already imported but their versions are earlier than the minimum required for Engage, the server automatically updates those dependencies to the latest available versions.

Required dependencies

Engage has the following required dependencies:

- Tanium™ Endpoint Configuration
- Tanium™ Interact
- Tanium™ Data Service (TDS)
- Tanium™ End-User Notifications
- Tanium™ RDB
- Tanium™ Reporting

Feature-specific dependencies

If you select only Engage to import, you must manually import or update its feature-specific dependencies regardless of Tanium Console or Tanium Core Platform versions. Engage has the

©2026 Tanium Inc. All Rights Reserved

following feature-specific dependencies at the specified minimum versions:

- Tanium™ Directory Query to collect user attributes to display in survey results.
- Tanium™ Criticality to collect user attributes to display in survey results.
- Tanium™ Performance to create performance-related surveys and to analyze employee sentiment based on performance scores.

Client extensions and endpoint tools

Tanium Endpoint Configuration installs Client Extensions and other tools for endpoints. Client extensions perform tasks that are common to certain Tanium solutions. Each Client Extension and tool might have recommended security exclusions to allow them to run without interference. For a list of all Client Extensions and tools, see Reference: Client extensions used for Tanium solutions.



Note: The change management feature of Endpoint Configuration might affect the version of each endpoint tool installed on endpoints.

Tanium™ Module Server

Engage is installed and runs as a service on the Module Server host computer. The impact on the Module Server is minimal and depends on usage.

For more information about Module Server sizing in a Windows deployment, see Tanium Core Platform User Guide for Windows Deployments: Host system sizing guidelines.

Endpoints

Supported operating systems

The following endpoint operating systems are supported with Engage.

©2026 Tanium Inc. All Rights Reserved

Supported operating systems for Tanium Engage

Operating System	Version
Microsoft Windows Workstation	• Windows 11 • Windows 10
macOS	macOS 11 Big Sur or later

Host and network security requirements

Specific ports and processes are needed to run Engage.

Ports

The following ports are required for Engage communication.

Port requirements

Source	Destination	Port	Protocol	Purpose
Module Server	Module Server (loopback)	17454	TCP	Internal purposes; not externally accessible



Best Practice: Configure firewall policies to open ports for Tanium traffic with TCP-based rules instead of application identity-based rules. For example, on a Palo Alto Networks firewall, configure the rules with service objects or service groups instead of application objects or application groups.

Security exclusions

If antivirus (AV) or other security software is in use in the environment to monitor and block unknown host system processes, Tanium requires that a security administrator create exclusions to allow the Tanium processes to run without interference. This software can include security applications that are included with an endpoint operating system, such as fapolicyd on some Linux distributions, or Microsoft Defender on Windows. The configuration of these exclusions varies depending on the security software.

For more information about security exclusions to define across Tanium, see Reference: Endpoint

©2026 Tanium Inc. All Rights Reserved

security exclusions. For Windows-based Tanium Core Platform deployments, see Tanium Core Platform Server security exclusions.

> **Note:** If the required exclusions are not configured, or if Tanium suspects interference from AV or security software, Tanium might require you to remove or disable the AV or security software temporarily for the purposes of troubleshooting and restore it once troubleshooting is complete.

ENGAGE ENDPOINT EXCLUSIONS

Engage security exclusions for endpoints

Endpoint OS	Notes	Exclusion Type	Exclusion
Windows		Process	*<Tanium Client>* \TaniumCX.exe
		File	*<Tanium Client>* \extensions\TaniumEndUser.dll
		Folder	<Parent of Tanium Client directory>\Tanium End User Notification Tools
macOS		Process	*<Tanium Client>* /TaniumCX
		Folder	/Library/Tanium/EndUserNotifications

ENGAGE SERVER EXCLUSIONS

Engage security exclusions for Tanium Core Platform servers (Windows deployments only)

Target Device	Notes	Exclusion Type	Exclusion
Module Server		Process	*<Module Server>* \services\engage-service\TaniumEngageService.exe

User role requirements

Predefined roles grant the following permissions, which are required to use Engage functionality:

©2026 Tanium Inc. All Rights Reserved

- solution permissions on page 17
- administration, platform content, and global permissions on page 19: The solution permissions automatically provide some of these permissions.

To review a summary of the predefined roles, see Set up Engage users on page 28.

Optional roles for on page 19 are required to enable optional Engage functionality.

Some Engage solution permissions provide permissions that are associated with other solutions. Furthermore, all the platform content permissions and some solution permissions apply to content sets that might contain content for other solutions in addition to Engage. If you create custom roles for Engage users, be sure to assign all the solution permissions and content set permissions that are required for Engage functionality. If you are not sure which permissions are required for a custom role, view the permissions of the predefined roles. For more information, see the following sections of the Tanium Console User Guide:

- RBAC overview (provides an overview of roles, permissions, and content sets)
- Provided role permissions
- View effective role permissions
- Configure a custom role

Note: Do not assign the **Engage Service Account** and **Engage Service Account - All Content Sets** roles to users. These roles are for internal purposes only.

Engage solution permissions

Permission	Engage Administrator [1]	Engage Operator [1]	Engage Question Author [1]	Engage Remediation Author [1]	Engage Theme Author [1]	Engage User [1]
Engage View the Engage workbench	✓ SHOW	✓ SHOW	✓ SHOW	✓ SHOW	✓ SHOW	✓ SHOW
Engage Questions Read and write access to Engage	✓ READ WRITE	✓ READ WRITE	✓ READ WRITE	✓ READ	✓ READ	✓ READ

©2026 Tanium Inc. All Rights Reserved

Permission	Engage Administrator [1]	Engage Operator [1]	Engage Question Author [1]	Engage Remediation Author [1]	Engage Theme Author [1]	Engage User [1]
survey questions						
Engage Remediations Read and write access to the Engage remediations	✓ READ WRITE	✓ READ WRITE	✓ READ	✓ READ WRITE	✗	✓ READ
Engage Settings Write access to platform settings in the Engage module	✓ READ	✓ READ WRITE	✓ READ	✓ READ	✓ READ	✓ READ
Engage Surveys Read and write access to Engage surveys	✓ AUTHOR OVERRIDE READ WRITE	✓ AUTHOR OVERRIDE READ WRITE	✓ READ	✓ READ	✓ READ	✓ AUTHOR READ WRITE
Engage Themes Read and write access to themes	✓ WRITE	✓ READ WRITE	✓ READ	✗	✓ READ WRITE	✓ READ

[1] The permissions for these roles provide solution permissions for other solutions. To view the provided permissions, see View effective role permissions .

©2026 Tanium Inc. All Rights Reserved

Engage administration and platform content permissions

Permission	Permission Type	Engage Administrator	Engage Operator	Engage Question Author	Engage Remediation Author	Engage Theme Author	Engage User
Action Group	Administration	READ	READ	READ	READ	READ	READ
Computer Group	Administration	READ	READ	READ	READ	READ	READ
Action	Platform Content	READ	READ	READ	READ	READ	READ
Filter Group	Platform Content	READ	READ	READ	READ	READ	READ
Package	Platform Content	READ WRITE	READ WRITE	READ	READ WRITE	READ	READ
Plugin	Platform Content	READ EXECUTE	READ EXECUTE	READ EXECUTE	READ EXECUTE	READ EXECUTE	READ EXECUTE
Sensor	Platform Content	READ	READ	READ	READ	READ	READ

To view the content sets to which the platform content permissions apply, see View effective role permissions .

Optional roles for Engage

Role	Enables
End-User Notifications Endpoint Configuration Operator	Manage most configurations and deployment of End-User Notifications functionality to endpoints.

©2026 Tanium Inc. All Rights Reserved

Getting started with Engage

Follow these steps to configure and use Engage.

Step 1: Configure Engage

1. For more information about setting up Engage, see Configuring Engage on page 25.
2. Control access to the platform and products by assigning users to groups and roles. For more information, see Tanium Console User Guide: RBAC overview and Configuring Engage on page 25.

Step 2: Create and schedule surveys

You can create surveys that include remediations for the end user to help solve problems with their endpoint. You can run and re-run surveys for specific time periods. For more information, see Creating surveys on page 31.

If you include a remediation in your survey, you can create custom remediation tasks in addition to using the default tasks that are provided. For more information, see Creating remediation tasks on page 46.

Step 3: Create and send notifications

Use notifications to notify employees of operational and service issues. You can also send notifications to communicate announcements about training, policy updates, and organizational changes. You can create and send a notification to targeted endpoints that can optionally include a remediation for the end user to help solve problems with their endpoint. For more information, see Creating notifications on page 63.

©2026 Tanium Inc. All Rights Reserved

Step 4: Analyze results

After your surveys run, you can look at the results. For more information, see View survey results on page 37 and Understanding employee sentiment on page 42.

©2026 Tanium Inc. All Rights Reserved

Installing Engage

Use Tanium Console **Solutions** page to install Engage and choose either automatic or manual configuration:

- Automatic configuration with default settings: Engage is installed with any required dependencies and other selected products. After installation, the Tanium Server automatically configures the recommended default settings. This option is the best practice for most deployments. For more information about the automatic configuration for Engage, see Import Engage with default settings on page 22.
- Manual configuration with custom settings: After installing Engage, you must manually configure required settings. Select this option only if Engage requires settings that differ from the recommended default settings. For more information, see Import Engage with custom settings on page 23.

Before you begin

- Read the release notes.
- Review the Engage requirements on page 12.
- Assign the correct roles to users for Engage. Review the User role requirements on page 16.
    - To import the Engage solution, you must be assigned the Administrator reserved role.
    - To configure the Engage action group, you must be assigned the Administrator reserved role, Content Administrator reserved role, or a role that has the **Action Group write** permission.

Import Engage with default settings

You can set the Engage action group to target the **No Computers** filter group by enabling restricted targeting before importing Engage. This option enables you to control Engage tools deployment

©2026 Tanium Inc. All Rights Reserved

through scheduled actions that are created during the import and that target the Engage action group. For example, you might want to test Engage tools on a subset of endpoints before deploying the Engage tools to all endpoints. In this case, you can manually deploy the Engage tools to an action group that you configured to target only the subset. To configure an action group, see Tanium Console User Guide: Managing action groups. To enable or disable restricted targeting, see Tanium Console User Guide: Tools deployment and restricted targeting.

To import Engage and configure default settings, see Tanium Console User Guide: Import all modules and services. After the import, verify that the correct version is installed. For more information, see Verify Engage version on page 24.

Default settings for Engage

When you import Engage with automatic configuration, the following default settings are configured:

Default settings

Setting	Default value
Action group	• Restricted targeting disabled (default): `All Computers` computer group • Restricted targeting enabled: `No Computers` computer group

Import Engage with custom settings

To import Engage without automatically configuring default settings, be sure to clear the **Apply All Tanium recommended configurations** checkbox while performing the steps in Tanium Console User Guide: Import or update specific solutions. After the import, verify that the correct version is installed. For more information, see Verify Engage version on page 24.

To organize computer groups, see Organize computer groups on page 28.

To configure the Engage action group, see Configure the Engage action group on page 27.

Other Tanium solutions are required for Engage to function (required dependencies) or for specific Engage features to work (feature-specific dependencies).

Upgrade Engage

For more information about the steps to upgrade Engage, see Tanium Console User Guide: Managing

©2026 Tanium Inc. All Rights Reserved

Tanium solutions. After the upgrade, verify that the correct version is installed: see Verify Engage version on page 24.

Verify Engage version

After you import or upgrade Engage , verify that the correct version is installed.

1. Refresh your browser.
2. From the Main menu, go to **Modules** > **Engage** to open the **Overview** page.
3. To show version information, click Info .

Troubleshoot issues

If you experience issues with installing Engage, see Troubleshooting Engage on page 72.

©2026 Tanium Inc. All Rights Reserved

Configuring Engage

If you did not install Engage with the **Apply All Tanium recommended configurations** option, you must enable and configure certain features.

Install and configure Tanium Endpoint Configuration

If you enabled configuration approvals, the following configuration changes must be approved in Endpoint Configuration before they deploy to endpoints:

- Creating, updating, or deleting surveys and notifications

Manage solution configurations with Tanium Endpoint Configuration

Tanium Endpoint Configuration delivers configuration information and required tools for Tanium Solutions to endpoints. Endpoint Configuration consolidates the configuration actions that traditionally accompany additional Tanium functionality and eliminates the potential for timing errors that occur between when a solution configuration is made and the time that configuration reaches an endpoint. Managing configuration in this way greatly reduces the time to install, configure, and use Tanium functionality, and improves the flexibility to target specific configurations to groups of endpoints.

Endpoint tools are bundled together in a versioned toolset. Each toolset contains a specific version of each tool. The Endpoint Configuration Toolset Solution provides upgrades to the toolset, and it imports upgraded versions of the entire toolset as needed by upgraded or newly installed solutions.

©2026 Tanium Inc. All Rights Reserved

Important:

When you upgrade Engage, the change management feature enables you to perform a staged rollout of the endpoint tools associated with the new version of Engage. Engage remains compatible with earlier versions of the endpoint tools and so continues to function with endpoints in rings that have not yet received the latest tools. However, any functionality added in the upgrade of Engage might not be available on these endpoints until they receive the upgraded tools.

In some cases, multiple solutions install the same endpoint tool, but upgraded endpoint tools remain compatible with all associated solutions. For example, both Tanium™ Threat Response and Tanium™ Reveal install and use index-cx. When you upgrade Threat Response, it might install version x.6.yyyy of index-cx, superseding version x.5.zzzz that Reveal previously installed. The index-cx upgrade from Threat Response does not affect the Index-related functionality of Reveal on the upgraded endpoints. For more information about the change management feature, see Tanium Endpoint Configuration User Guide: Managing endpoint tool upgrade rollouts.

Note: For information about how to install Endpoint Configuration, see Installing Endpoint Configuration.

Optionally, you can use Endpoint Configuration to require approval of configuration changes. When configuration approvals are enabled, Endpoint Configuration does not deploy a configuration change to endpoints until a user with approval permission approves the change. For information about the roles and permissions that are required to approve configuration changes for Engage, see User role requirements. For more information about how to enable and use configuration approvals in Endpoint Configuration, see Managing approvals.

Important: For solutions to perform configuration changes or tool deployment through Endpoint Configuration on endpoints with action locks turned on, you must enable the **Manifest Package Ignore Action Lock** and **Deploy Client Configuration and Support Package Ignore Action Lock** settings. To access these settings, from the Endpoint Configuration **Overview** page, click Settings and select **Global**. For more information about action locks, see Managing action locks.

©2026 Tanium Inc. All Rights Reserved

For more information about Endpoint Configuration, see Tanium Endpoint Configuration User Guide.

Install and configure Tanium End-User Notifications

Tanium End-User Notifications is a shared service that is used to send notifications to users, including sending Engage surveys and notifications. You must configure end-user notifications and customize the End-User Self Service interface before you configure Engage. For more information, see Tanium End-User Notifications User Guide: Configuring and Tanium End-User Notifications User Guide: Customizing the End-User Self Service interface. Configure any exclusions that are listed in the Tanium End-User Notifications User Guide: Security Exclusions. You can customize the self-service interface to match your corporate branding.

Configure Engage

Configure the Engage action group

About this task

Importing the Engage module automatically creates an action group to target specific endpoints. If you did not use automatic configuration or you enabled restricted targeting when you imported Engage, the action group targets **No Computers**.

If you used automatic configuration and restricted targeting was disabled when you imported Engage, configuring the Engage action group is optional.

Select the computer groups to include in the Engage action group.

Best Practice: Clear the selection for **No Computers** and make sure that all operating systems that are supported by Engage are included in the Engage action group.

1. From the Main menu, go to **Administration** > **Actions** > **Action Groups**.
2. Click Tanium Engage.
3. Select the computer groups that you want to include in the action group and click **Save**. If you select multiple computer groups, choose an operator (AND or OR) to combine the groups.

©2026 Tanium Inc. All Rights Reserved

Organize computer groups

1. Determine which endpoints receive endpoints with computer group targeting. Create relevant computer groups to organize your endpoints. Some options include:
    - Endpoint type, employee workstations
    - Endpoint location, such as by country or time zone
2. Add the computer groups to the appropriate users or user groups so that the survey and notification creators can schedule surveys and notifications to run on those endpoints. For more information, see Tanium Core Platform User Guide: Managing computer groups.

Set up Engage users

You can use the following set of predefined user roles to set up Engage users.

For more information about permissions for each role, see User role requirements on page 16.

Important: On installation, Engage creates an Engage user to automatically manage the Engage service account. Do not edit or delete the Engage user.

For more information about assigning user roles, see Tanium Core Platform User Guide: Manage role assignments for a user.

Tip: To provide just-in-time access or scalable standing access to Engage functionality, you can use SCIM provisioning combined with Tanium user groups. This approach lets you manage user access at scale or ad hoc through your identity provider, without creating users individually in Tanium. For more information, see Provision users into Tanium user groups with SCIM.

Engage Administrator

Assign the **Engage Administrator** role to users who manage the configuration and deployment of Engage functionality to endpoints. This role can perform the following tasks:

- Configure Engage service settings.
- View and modify Engage surveys, survey question, notifications, and remediations.

©2026 Tanium Inc. All Rights Reserved

- View and modify themes.
- Dismiss or reject approvals for Engage tasks in Tanium Endpoint Configuration.

Engage Operator

Assign the **Engage Operator** role to users who manage the configuration and deployment of Engage functionality to endpoints. This role can perform the following tasks:

- Configure Engage service settings.
- View and modify Engage surveys, survey questions, notifications, and remediations.
- View and modify themes.
- Dismiss or reject approvals for Engage tasks in Tanium Endpoint Configuration.

Engage Question Author

Assign the **Engage Question Author** role to users who need to create surveys and survey question templates. This role can perform the following tasks:

- View Engage workbench, settings, remediations, surveys, and notifications.
- View themes
- Author and edit Engage questions.

Engage Remediation Author

Assign the **Engage Remediation Author** role to users who need to create remediations for surveys, notifications, and survey question templates. This role can perform the following tasks:

- View Engage workbench, settings, surveys, survey questions, and notifications.
- Author and edit Engage remediations.

Engage Theme Author

Assign the **Engage Theme Author** role to users who need to create themes. This role can perform the following tasks:

- View surveys, survey questions, remediations, and notifications.

©2026 Tanium Inc. All Rights Reserved

- View and create themes.

Engage User

Assign the **Engage User** role to users who need visibility into Engage data and the ability to create surveys. This role can perform the following tasks:

- View and modify Engage surveys.
- View survey questions, remediations, and notifications.
- View settings.

Engage Read Only User

Assign the **Engage Read Only User** role to users who only need to view Engage data. This role can perform the following tasks:

- View Engage workbench, settings, surveys, survey questions, notifications, and remediations.

> **Note:** Do not assign the **Engage Service Account** and **Engage Service Account - All Content Sets** roles to users. These roles are for internal purposes only.

©2026 Tanium Inc. All Rights Reserved

Creating surveys

A survey can contain up to five questions. You can send surveys to targeted groups of users, based on endpoint trigger conditions. If you define trigger conditions for a survey, you can also include remediations in the last survey question.

When the endpoint meets the conditions for a survey, the survey displays to the endpoint user as a notification. If the user postpones the survey, they can later access the survey in the End-User Self Service Interface. For more information, see Tanium End-User Notifications User Guide: Customizing the End-User Self Service interface.

Note: For endpoints that have multiple users, notifications appear for every user as long as the trigger conditions are true.

For more information about example scenarios, see Survey examples.

Create survey

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. Click **Create Survey** and then select an option from the list.
   - **Blank Survey**: Start with a blank form and complete the fields to build a new survey.
   - **From Template**: Load a survey template that includes predefined trigger conditions, survey questions, and remediation tasks. You can refine the survey properties to suit your needs. The following templates are available by default:

Survey templates

Template name	Use case	Remediation task
Browser Security - Chrome	Target endpoints with pending updates for Google Chrome.	Task: Restart Google Chrome

©2026 Tanium Inc. All Rights Reserved

Template name	Use case	Remediation task
Browser Performance - Chrome [1]	Suggest users to restart Chrome to improve browser performance.	Task: Restart Google Chrome
Device Performance	Collect and measure employee sentiment about system performance.	None
IT Policy	Confirm your employees have read and understood your organization's IT policy.	Link: <Add a related link to your company site>
Low Disk Space	Target endpoints with low disk space to maintain optimal system performance and prevent future issues. For example, endpoints with less than 5 GB on the C drive often cannot update the operating system, which can create security risks.	Task: User Disk Cleanup
Reboot Suggested	Suggest a reboot for endpoints that have not restarted within the last 30 days.	Task: Restart Endpoint
Recent Software Upgrades	Collection and measure employee sentiment after recent software upgrades.	None
Workstation Performance [1]	Measure employee sentiment regarding performance on devices with low performance scores.	None

[1] Requires the Tanium Performance solution.

3. Give the survey a title, optional description, and select an original language. The title appears to the user in the notification on the endpoint.
4. If you do not want to use the default content set, select a **Content Set**. Every survey requires a content set. If no content set is available, you might need additional permissions. For more information, see Tanium Console User Guide: Role permissions for content sets.
5. (Optional) Define trigger conditions. A trigger condition defines when the end user of the endpoint gets prompted to take the survey. The trigger condition can be based on a Tanium

©2026 Tanium Inc. All Rights Reserved

sensor or performance metric. If you do not define trigger conditions, the survey is sent to end users on all targeted endpoints; you define targets when you schedule the survey.

a. Click **Add Condition**, then click **+ Row** or **+ Group** to define the trigger condition.
b. Click **Apply** ✓ to save the condition, then click **Save**.
c. In **Minimum time between survey notifications**, specify the amount of time between survey notifications that the user receives on the endpoint. By default, the survey notification is every 24 hours.

6. Click **Add Survey Questions**. You can either create a new question or select an existing question template. If you create a new question while you are creating the survey, you can add the question to this survey only, or save the question as a template. For more information about managing question templates, see Create question templates on page 39.
7. If you are creating a question, you can add the question details, and text.
8. Create answers to the question. Choose between multiple choice or sentiment score answer types:
   Multiple choice: A question that provides up to 10 answers from which the user can select one answer.

   Sentiment: A question that collects data about the user's feelings. The user responses to sentiment questions contribute to the employee sentiment score.

   The sentiment score is calculated on a 1-5 Likert scale rating about the user's feelings (5: Strong Positive, 1: Strong Negative). The overall sentiment score is a scaled average of all sentiment score questions across all surveys that have sentiment questions, and gets a rating based on the following calculations:

   - Strong Positive: 87.5-100
   - Positive: 62.5-87.4
   - Neutral: 37.5-62.4
   - Negative: 12.5-37.4
   - Strong Negative: 0-12.4
9. Add remediations. A multiple choice answer can have up to ten multiple choice answers and a link or task remediation. A sentiment answer can have a link remediation.

©2026 Tanium Inc. All Rights Reserved

Important: You can include remediations only in the last question of a survey.

- A link that opens a link for the user, for example, to open a ticket with the IT help desk. The link must start with `https://`.
- A task to deploy to the endpoint when the associated response is selected. You can choose from the following pre-defined tasks:

  Restart Endpoint
  Restarts the target device.

  Clear Microsoft Teams Cache
  Clears cache to resolve problems with Microsoft Teams.

  Clear DNS Cache
  Clears DNS cache to help resolve network issues.

  Enable / Disable Fast Start
  Enables or disables the Windows OS Fast Start feature.

  Restart <application>
  Restarts the (macOS) Apple Safari, Cisco Webex, Google Chrome, Microsoft Edge, Microsoft Outlook, Microsoft Teams, Mozilla Firefox, Slack, or Zoom application.

  User Disk Cleanup
  Performs light (Recycle bin empty) clean.

  Tip: You can also create custom remediation tasks from another Tanium package. For more information, see Creating remediation tasks on page 46.

10. (Optional) Add multi-language support. Click **Add Languages**, select one or more languages, expand each language you selected, and enter the translated text. The default survey language is based on the locale and OS of the user.

    Tip: The **Add Languages** option is disabled until you add a survey title and unique questions. If you include a question with a remediation, you must also specify trigger conditions to enable the **Add Languages** options.

©2026 Tanium Inc. All Rights Reserved

11. Save the survey. You can either save the survey as a draft or save and schedule the survey to run. To save the survey as a draft, it must have at least a title and one survey question.

Schedule survey run

About this task

When you create a survey, it is in draft mode until you schedule it to run. When a survey is running, the survey is collecting feedback from the targeted endpoints.

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. Click the name of the survey that you want to schedule.
    - If the survey has a **Draft** status, the **Edit survey page** appears and you can edit the schedule.
    - If the survey has a **Done** status, click **Run survey again** to edit the schedule.
    - If the survey has a **Scheduled** or **Running** status, click **End Current Run** and then **Run survey again** to edit the schedule.
3. Set a **Start Time** and **End Time**. The **End Time** includes the following options:
    - **Scheduled**: Set a date and time for the survey to stop running.
    - **None**: Do not set an end time and let the survey run indefinitely.

      You can also choose to use UTC (default) or the endpoint local time to schedule the survey.
4. Choose endpoints to target with the survey. You can select computer groups to receive the survey.
   The user that creates the survey or notification must have management rights to this computer group. For more information about assigning computer groups to a user, see Tanium Platform User Guide: Manage computer group assignments for a user.
5. Choose user options for the survey, including whether they can postpone or decline the survey. You can also enable anonymous responses to the survey, so no user information is recorded from the responses.
6. Click **Run Survey**. If you want to end a survey while it is running, click **End Current Run**.

©2026 Tanium Inc. All Rights Reserved

View existing survey status

You can view the latest surveys on the **Engage Overview** page. To view all surveys, from the Engage menu, go to **Surveys**.

Survey status icons

Status	Description
	The survey is in draft mode. Finish editing and schedule the survey run.
	The survey is currently running and collecting feedback from targeted endpoints.
	The survey is scheduled to run at a future date and time.
	The survey is done. You can run the survey again by editing the schedule.
	An error occurred when scheduling or sending the survey.

End user survey experience

While the survey is running, all targeted endpoints receive the survey. The end user receives the survey as a notification on their endpoint. The user can take one of the following actions:

- Take the survey.
- Postpone the survey, if the **Allow user to postpone survey** setting is enabled. The end user gets notified about the survey again at the scheduled interval.
- Decline the survey, if the **Allow user to decline survey** setting is enabled. The user is not notified about the survey again.
- Close the window or shut down the endpoint. The notification is not shown again. The end user must view the survey in the End-User Self Service Interface.
- Take no action. The notification stays on the screen.
- View the survey in the End-User Self Service Interface. The survey is listed in this interface,

©2026 Tanium Inc. All Rights Reserved


even if the user declined or postponed the survey.

View survey results

1. From the Engage home page or the **Surveys** page, click the name of the survey that you want to view.
2. If you want to change the results to a previous run, select a run from **Survey Runs**.
3. The **Survey Results** section shows a summary of the endpoints that received the survey and the users that responded to the survey. The following survey results are available:

Survey results

Result	Description
not notified	The survey is not started, waiting for trigger condition to evaluate `true` , or waiting to notify the user.
notified	The user was notified. After notification, the survey will show `no response` until the user acknowledges the notification or submits a response.
responded	The user responded to a survey.
acknowledged	The user acknowledged a push notification.
postponed	The user postponed a survey.
dismissed	The user dismissed a survey.
no response	The survey ended with no response from the user, or the user did not yet interact with an active survey or notification.



4. View details about survey responses from users in the **Responses** section.

©2026 Tanium Inc. All Rights Reserved

5. To view the survey questions, expand the **Survey Questions** section.

View survey responses for a single endpoint

About this task

You can view survey results for a single endpoint through the Endpoint Details page in Tanium™ Reporting. To view survey results, you must have **Engage Surveys read** permission.

1. Open the Endpoint Details page for the endpoint that requires survey details. For more information, see Tanium Reporting User Guide: View endpoint details.
2. Select the **Engage** tab.
3. In the **Survey Responses** section, view survey results, responses, performance score, sentiment score, and so on.

Run survey again

About this task

You can re-run a survey that is in the Done state. You can change the schedule, options, and endpoints that are targeted with survey. If you want to change any survey questions, you must create a new survey.

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. Click the name of the survey that you want to run again.
3. Click **Run Survey Again**.
4. Set a **Start Time** and **End Time**. The **End Time** includes the following options:
   - **Scheduled**: Set a date and time for the survey to stop running.
   - **None**: Do not set an end time and let the survey run indefinitely.

     You can also choose to use UTC (default) or the endpoint local time to schedule the survey.
5. Choose endpoints to target with the survey. You can select computer groups to receive the survey. For more information about configuring computer groups for Engage, see Organize

©2026 Tanium Inc. All Rights Reserved

computer groups on page 28.

6. Choose user options for the survey, including whether they can postpone or decline the survey.
7. Click **Run Survey**. If you want to end a survey while it is running, click **End Current Run**.

Create question templates

About this task

To create questions that you can reuse in multiple surveys, create survey question templates.

1. From the Main menu, go to **Modules** > **Engage > Survey Question Templates**.
2. Click **Create Question Template**.
3. Add the question details, text, choices and a remediation for one of the answers. The remediation can provide a URL to open when the associated response is selected.
4. If you do not want to use the default content set, select a **Content Set**. Every question template requires a content set. If no content set is available, you might need additional permissions. For more information, see Tanium Console User Guide: Role permissions for content sets.
5. (Optional) Add multi-language support. Click **Add Languages**, select one or more languages, expand each language you selected, and enter the translated text.

   Tip: The **Add Languages** option is disabled until you enter the question text, unique answers, and select any remediations.
6. When finished with the question template, click **Submit**.
7. You can add the question to a survey when you add questions. During the survey creation process, click **Add Survey Questions** > **Choose Existing**.

Result

Important: After you add a question based on a survey template to a survey, you can no longer edit the question in the survey by editing the survey question template.

©2026 Tanium Inc. All Rights Reserved

Export and import surveys

You can export surveys from one environment and import them to another environment. For example, export surveys from a test environment and import them to a production environment.

Note: Surveys with custom remediations cannot be exported.

Export survey

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. To export all surveys, click **Export All**.

   Tip:

   To export a subset of surveys, select one or more surveys and then click **Export**. You can also export an individual survey by clicking **Export** in the View Details panel.

Result

A JSON file downloads to the browser download folder.

Import survey

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. To import previously exported surveys, click **Import** and then provide the previously downloaded JSON file.

Result

If you import a survey that has the same name as an existing survey, Engage appends **[<#>]** to the name of the imported survey. For example, if **Survey_Name** already exists, then Engage imports it as **Survey_Name [1]**.

Clone survey

©2026 Tanium Inc. All Rights Reserved

About this task

Clone an existing survey to create similar surveys or to run a survey again. You can clone surveys that are in the **Running** or **Done** state.

1. From the Main menu, go to **Modules** > **Engage > Surveys**.
2. Select the survey that you want to clone by using one of the following methods:
    - Click the name of the survey. The **Survey Details** page appears.
    - Select the checkbox for the survey. The Clone icon  appears in the **Surveys** grid header.
3. Click Clone  and then edit the survey details.
4. Save the survey. You can either click **Save as Draft** or **Save and Schedule Run**.

©2026 Tanium Inc. All Rights Reserved

Understanding employee sentiment

About this task

To understand employee sentiment, analyze the digital employee experience (DEX) data, which is derived from sentiment scores and performance scores.

> **Note:** This topic includes information about performance scores. Performance scores require the Tanium Performance solution.

Overall employee sentiment score

Employee sentiment is collected from sentiment questions in surveys.

The sentiment score is calculated on a 1-5 Likert scale rating about the user's feelings (5: Strong Positive, 1: Strong Negative). The overall sentiment score is a scaled average of all sentiment score questions across all surveys that have sentiment questions, and gets a rating based on the following calculations:

- Strong Positive: 87.5-100
- Positive: 62.5-87.4
- Neutral: 37.5-62.4
- Negative: 12.5-37.4
- Strong Negative: 0-12.4

To start getting employee sentiment information, create surveys that include sentiment questions. For more information, see Creating surveys on page 31.

Scope performance and sentiment scores

About this task


©2026 Tanium Inc. All Rights Reserved

You can view the sentiment and performance across all surveys, or for a specific survey, computer group, or time frame.

1. From the Engage menu, go to **Employee Sentiment**. Without any scoping, the data includes performance score data for all endpoints, and all surveys that include a sentiment question.
2. Scope results for a survey. From **Surveys**, select a survey. If multiple survey runs have the same title, a timestamp showing when the survey was last updated appears below the title.
3. Scope results for computer groups. The `All Computers` computer group is selected by default. From **Computer Group**, select a computer group.
4. Scope results by date. From **Timeframe**, select a date. To choose specific dates, select **Custom**.

Review metric summary

Figure 1. Employee Sentiment page



©2026 Tanium Inc. All Rights Reserved

Overall Response Rate

The overall response rate is the percentage of endpoints that had a user complete surveys that were pushed to that endpoint. If the user dismissed, did not respond, or postponed the survey, the response is considered incomplete.

Employee Response

The employee response chart shows the count of responses from the surveys that got pushed to the endpoints. The responses can be: no response, dismissed, postponed, or responded.

Total Responses by Sentiment

Number of responses for each sentiment on the Likert scale (5: Strong Positive, 1: Strong Negative).

Employee Sentiment Score

The employee sentiment score shows an average sentiment of all sentiment-based survey questions that are scoped in the selection.

Endpoint Performance Score

The average performance score shows the overall health of all endpoints that are scoped in the selection. For more information about how performance scores get calculated, see Tanium Performance Overview: Performance scores.

DEX Scores Over Time

The DEX Scores Over Time chart shows a line graph, so that you can compare endpoint performance to employee sentiment scores.


View digital employee experience (DEX) on a single endpoint

About this task

You can view DEX details for a single endpoint through the Endpoint Details page in Tanium™ Reporting. To view survey results, you must have **Engage Surveys read** permission.

©2026 Tanium Inc. All Rights Reserved

Figure 2. Digital employee experience for an endpoint



1. Open the Endpoint Details page for the endpoint that requires survey details. From the **Employee Sentiment** page, you can click a **Computer Name** to get to the details for that endpoint. For more information about how to get to single endpoint views, see Tanium Reporting User Guide: View endpoint details.
2. Select the **Engage** tab.
3. In the **Digital Employee Experience** section, view how many survey notifications and responses were on the endpoint, sentiment score, performance score, and so on.

©2026 Tanium Inc. All Rights Reserved

Creating remediation tasks

You can include remediations when you create surveys and notifications. When you create a survey, one question can include a remediation task that the endpoint user can choose to run to resolve an issue. When you create a notification, you can include a remediation that triggers when users acknowledge the notification. In addition to the default remediation packages that are included with Engage, you can define your own custom remediation tasks that use existing Tanium packages, or packages that you define.

Default remediation tasks

The following remediation tasks are included with Engage.

Restart Endpoint

Restarts the target device.

Clear Microsoft Teams Cache

Clears cache to resolve problems with Microsoft Teams.

Clear DNS Cache

Clears DNS cache to help resolve network issues.

Enable / Disable Fast Start

Enables or disables the Windows OS Fast Start feature.

Restart <application>

Restarts the (macOS) Apple Safari, Cisco Webex, Google Chrome, Microsoft Edge, Microsoft Outlook, Microsoft Teams, Mozilla Firefox, Slack, or Zoom application.

User Disk Cleanup

Performs light (Recycle bin empty) clean.

©2026 Tanium Inc. All Rights Reserved

Create remediation package

Before you create a remediation task, choose or create a package that you want to deploy as a part of the remediation task.

Tanium packages

To browse the packages that are already in your environment, go to **Administration** > **Packages**.



Important: You cannot use sensor-sourced packages as a remediation task. Sensor-sourced packages include a sensor name with pipe characters in the package command, for example: `||Reveal - Confirmed Files_File||`

Custom package

To create a custom package that runs as user, see the following samples:

- Sample: (Windows with PowerShell Script and Notepad) Create remediation package that runs as user on page 48
- Sample: (Windows with PowerShell Script) Create remediation package that runs as user on page 52
- Sample: (macOS with Shell Script and TXT File) Create remediation package that runs as user on page 56
- Sample: (macOS with Shell Script) Create remediation package that runs as user on page 58

For more information about creating and managing packages, see Tanium Console User Guide: Managing packages.

Create remediation task

1. From the Main menu, go to **Modules** > **Engage > Remediations**.
2. Click **Create Task**.

©2026 Tanium Inc. All Rights Reserved

3. Enter a name, description, and content set to which you want to save the remediation task.
4. Click **Add Package** and choose a package to run.
5. Save your changes.

Sample: (Windows with PowerShell Script and Notepad) Create remediation package that runs as user

Use this sample to create a task that runs as the user answering the survey on a Windows endpoint. This script uses the TaniumRunAsUser.exe utility that ships with the Engage tools.

1. This sample includes a script that opens Notepad in the user context on the endpoint. Create the OpenNotepadAsUser.ps1 file by copying and pasting the following code into a text file.

```
param (
    # The SID of the user
    [Parameter(Position = 0, Mandatory = $true)]
    [string]$UserSID
)

$UserSID = [system.uri]::UnescapeDataString( $UserSID )

function Get-SessionFromSid( [string] $UserSID) {
    # Assume that the user has explorer.exe running
    foreach ( $process in (Get-CimInstance Win32_Process -filter "name =
'explorer.exe'")) {
        $owners = (Invoke-CimMethod -InputObject $process -MethodName GetOwnerSid)
        foreach ($owner in (Where-Object -InputObject $owners -Property ReturnValue
-EQ 0)) {
            if ($UserSID -eq $owner.SID) {
                return $process.SessionId
            }
        }
    }
}

# you should check that this is not $null and exit gracefully
```

©2026 Tanium Inc. All Rights Reserved

```
$sessionId = Get-SessionFromSid $UserSID
if ($sessionId -eq $null) {
    Write-Error "Could not find session for user SID: $UserSID"
    exit 1
}

# Take note of the extra quotes around the inner command
$command = "cmd.exe /d /c start ""C:\Windows\notepad.exe"""

# Note: /sessionid=<value> is one group
#       /cmd is one group, and has more quotes around $command
#       /userenv ensures that we will load the user's environment variables
$arguments = ("/noconsole", "/wrap", "/userenv", "/sessionid=$sessionId", "/cmd
""$command""")


$fileName = "$Env:TANIUM_CLIENT_ROOT\Tools\Engage\tasks\TaniumRunAsUser.exe"
Start-Process -FilePath $fileName -ArgumentList $arguments
```

©2026 Tanium Inc. All Rights Reserved


Important:

Follow these guidelines in your script to prevent potential security issues, such as privilege escalation or malicious code execution:

- The TaniumRunAsUser.exe file should be run from the default Tanium Client path, at: <Tanium Client>\Tools\Engage\tasks\TaniumRunAsUser.exe. Use the path exactly as it is provided in the OpenNotePadAsUser.ps1 code sample.
- Any commands that run from within your package file should run from explicitly specified paths that are not writable by non-admin users. For example, the following command includes a path that is not writable: `"<Tanium Client>\Tools\Engage\tasks\TaniumRunAsUser.exe" /noconsole /wrap /userenv /sessionid= /cmd "cmd.exe /d /c start "non\user\writable\path\TARGET_PROCESS"`
- If the TaniumRunAsUser.exe command is run with the `/userenv` switch, environment variables that are referenced from within the TARGET_PROCESS resolve to the target user's environment variables. Avoid executing scripts or executable files from within the TARGET_PROCESS using an unreliable path. A path that references user environment variables can lead to execution of unintended files.
- The self-authored package file code should validate package parameters before appending them directly to other commands.

2. Create the package in Tanium Console. From the Main menu, go to **Administration** > **Packages** > **New Package**.
3. Enter the package details.

©2026 Tanium Inc. All Rights Reserved



a. In the **Command** field, enter the following command: `cmd.exe /d /c powershell.exe -ExecutionPolicy Bypass -WindowStyle Hidden -NonInteractive -NoProfile -File OpenNotepadAsUser.ps1 $1`

b. Verify that **Launch this package command in a process group** is not selected.

c. Click **Add File** and upload the OpenNotepadAsUser.ps1 file.

d. Click **Add Parameter** > **Text Input**.

e. In the **Label** field, enter `USER_SID`.

f. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_SID`. Click **Save**.

©2026 Tanium Inc. All Rights Reserved

> **Important:** This specific parameter placeholder, PARAM_USER_SID, is replaced with the actual user security identifier (SID) at runtime only when run as a remediation task through Engage. If you want to use this package outside of Engage, you need to manually provide the actual identifier value.

4. Choose this package when you create your remediation task. For more information, see Create remediation task on page 47.

Sample: (Windows with PowerShell Script) Create remediation package that runs as user

Use this sample to create a task that runs as the user answering the survey on a Windows endpoint. This script uses the TaniumRunAsUser.exe utility that ships with the Engage tools.

1. This sample script runs a PowerShell script in the user context on the endpoint. Create the RunPowershellScriptAsUser.ps1 file and paste the following code into the file.

```
param (
    # The SID of the user
    [Parameter(Position = 0, Mandatory = $true)]
    [string]$UserSID
)

$UserSID = [system.uri]::UnescapeDataString( $UserSID )

function Get-SessionFromSid( [string] $UserSID) {
    # Assume that the user has explorer.exe running
    foreach ( $process in (Get-CimInstance Win32_Process -filter "name =
'explorer.exe'")) {
        $owners = (Invoke-CimMethod -InputObject $process -MethodName GetOwnerSid)
        foreach ($owner in (Where-Object -InputObject $owners -Property ReturnValue
-EQ 0)) {
            if ($UserSID -eq $owner.SID) {
                return $process.SessionId
            }
        }
```

©2026 Tanium Inc. All Rights Reserved

```
    }
}

# you should check that this is not $null and exit gracefully
$sessionId = Get-SessionFromSid $UserSID
if ($sessionId -eq $null) {
    Write-Error "Could not find session for user SID: $UserSID"
    exit 1
}

# Take note of the extra quotes around the inner command
$command = "powershell.exe -NoProfile -ExecutionPolicy bypass -File
.\TestPowerShellScript.ps1"

# Note: /sessionid=<value> is one group
#       /cmd is one group, and has more quotes around $command
#       /userenv ensures that we will load the user's environment variables
$arguments = ("/noconsole", "/wrap", "/userenv", "/sessionid=$sessionId", "/cmd
""$command""")

$fileName = "$Env:TANIUM_CLIENT_ROOT\Tools\Engage\tasks\TaniumRunAsUser.exe"
Start-Process -FilePath $fileName -ArgumentList $arguments
```

©2026 Tanium Inc. All Rights Reserved


Important:

Follow these guidelines in your script to prevent potential security issues, such as privilege escalation or malicious code execution:

- The TaniumRunAsUser.exe file should be run from the default Tanium Client path, at: <Tanium Client>\Tools\Engage\tasks\TaniumRunAsUser.exe. Use the path exactly as it is provided in the RunPowershellScriptAsUser.ps1 code sample.
- Any commands that run from within your package file should run from explicitly specified paths that are not writable by non-admin users. For example, the following command includes a path that is not writable: `"<Tanium Client>\Tools\Engage\tasks\TaniumRunAsUser.exe" /noconsole /wrap /userenv /sessionid= /cmd "cmd.exe /d /c start "non\user\writable\path\TARGET_PROCESS"`
- If the TaniumRunAsUser.exe command is run with the `/userenv` switch, environment variables that are referenced from within the TARGET_PROCESS resolve to the target user's environment variables. Avoid executing scripts or executable files from within the TARGET_PROCESS using an unreliable path. A path that references user environment variables can lead to execution of unintended files.
- The self-authored package file code should validate package parameters before appending them directly to other commands.

2. In the RunPowershellScriptAsUser.ps1 file, replace the command variable `RunPowershellScriptAsUser.ps1` with your PowerShell script file.
3. Create the package in Tanium Console. From the Main menu, go to **Administration** > **Packages** > **New Package**.
4. Enter the package details.

©2026 Tanium Inc. All Rights Reserved



a. In the **Command** field, enter the following command: `cmd.exe /d /c powershell.exe -ExecutionPolicy Bypass -WindowStyle Hidden -NonInteractive -NoProfile -File RunPowershellScriptAsUser.ps1 $1`

b. Verify that **Launch this package command in a process group** is not selected.

c. Click **Add File** and upload the RunPowershellScriptAsUser.ps1 file.

d. Click **Add File** and upload your PowerShell script file.

e. Click **Add Parameter** > **Text Input**.

f. In the **Label** field, enter `USER_SID`.

©2026 Tanium Inc. All Rights Reserved

g. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_SID`. Click **Save**.

> **Important:** This specific parameter placeholder, PARAM_USER_SID, is replaced with the actual user security identifier (SID) at runtime only when run as a remediation task through Engage. If you want to use this package outside of Engage, you need to manually provide the actual identifier value.

5. Choose this package when you create your remediation task. For more information, see Create remediation task on page 47.

Sample: (macOS with Shell Script and TXT File) Create remediation package that runs as user

Use this sample to create a task that runs as the user answering the survey on a macOS endpoint.

1. This sample script writes the user's home directory to a text file. Create the run-as-user-sample.sh file and paste the following code into the file:

```
#!/bin/sh
#@INCLUDE=i18n/UTF8Decode.sh
#@START_INCLUDES_HERE


user_id=$(utf8decode "$1")
username=$(utf8decode "$2")

launchctl asuser ${user_id} sudo -Hu ${username} /bin/sh -c 'echo $HOME >> $HOME/
echoed.txt'
```

2. Create the package in Tanium Console. From the Main menu, go to**Administration** > **Packages** > **New Package**.

3. Enter the package details.

©2026 Tanium Inc. All Rights Reserved



a. In the Command field, enter the following command: `/bin/sh run-as-user-sample.sh $1 $2`

b. Verify that **Launch this package command in a process group** is not selected.

c. Click **Add File** and upload the run-as-user-sample.sh file.

d. Click **Add Parameter** > **Text Input** to define the first input, $1.

e. In the **Label** field, enter `User ID`.

f. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_ID`.

©2026 Tanium Inc. All Rights Reserved

g. Click **Add Parameter** > **Text Input** to define the second input, $2.

h. In the **Label** field, enter `Username`.

i. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_NAME`. Click **Save**.

> **Important:** The specific parameter placeholders, PARAM_USER_ID and PARAM_USER_NAME, are replaced with the actual user identifier and username at runtime only when run as a remediation task through Engage. If you want to use this package outside of Engage, you need to manually provide the actual values for the user identifier and username.

4. Choose this package when you create your remediation task. For more information, see Create remediation task on page 47.

Sample: (macOS with Shell Script) Create remediation package that runs as user

Use this sample to create a task that runs as the user answering the survey on a macOS endpoint.

1. This sample script runs a Shell script in the user context on the endpoint. Create the RunScriptAsUser.sh file and paste the following code into the file:

```
#!/bin/sh


awk_script='
function hex_to_octal(hex) {
decimal=hex_to_decimal(hex)
return sprintf("\\0%03o", decimal)
}


function hex_to_decimal(value, result) {
for(j=1; j<=length(value); j++) {
result=(result*16) + HEX[substr(value, j, 1)]
}
return(result)
```

©2026 Tanium Inc. All Rights Reserved

```
}

function convert(s) {
while(match(s, /%../)) {
encoded=substr(s, RSTART, RLENGTH)
sub(encoded, hex_to_octal(encoded), s)
}
return s
}

BEGIN {
HEX["0"] = 0
HEX["1"] = 1
HEX["2"] = 2
HEX["3"] = 3
HEX["4"] = 4
HEX["5"] = 5
HEX["6"] = 6
HEX["7"] = 7
HEX["8"] = 8
HEX["9"] = 9
HEX["a"] = 10
HEX["b"] = 11
HEX["c"] = 12
HEX["d"] = 13
HEX["e"] = 14
HEX["f"] = 15
HEX["A"] = 10
HEX["B"] = 11
HEX["C"] = 12
HEX["D"] = 13
HEX["E"] = 14
HEX["F"] = 15
}

{
```

©2026 Tanium Inc. All Rights Reserved

```
printf("%s\n", convert($0))
}
'

usable_awk() {
if found=`command -v nawk`; then
echo "$found"
return
fi

if [ -x /usr/xpg4/bin/awk ]; then
echo /usr/xpg4/bin/awk
return
fi

command -v awk
}

utf8decode() {
awk_bin=`usable_awk`
printf "%b\n" "`echo "$1" | $awk_bin "$awk_script"`"
}

user_id=$(utf8decode "$1")
username=$(utf8decode "$2")

if [ -z ${username} ]; then
echo "No username specified."
usage
fi

if [ -z ${user_id} ]; then
echo "No user id specified."
usage
fi
```


©2026 Tanium Inc. All Rights Reserved

```
launchctl asuser ${user_id} sudo -Hu ${username} /bin/sh ./TestScript.sh
```

2. In the RunScriptAsUser.sh file, replace the command variable `TestScript.sh` with your Shell script file.

3. Create the package in Tanium Console. From the Main menu, go to **Administration** > **Packages** > **New Package**.

4. Enter the package details.



   a. In the Command field, enter the following command: `/bin/sh RunScriptAsUser.sh $1 $2`

   b. Verify that **Launch this package command in a process group** is not selected.

   c. Click **Add File** and upload the RunScriptAsUser.sh file.

©2026 Tanium Inc. All Rights Reserved

d. Click **Add File** and upload your Shell script file.

e. Click **Add Parameter** > **Text Input** to define the first input, $1.

f. In the **Label** field, enter `User ID`.

g. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_ID`.

h. Click**Add Parameter** > **Text Input** to define the second input, $2.

i. In the **Label** field, enter `Username`.

j. In the **Options** list, select **Provide Default Value** and then enter `PARAM_USER_NAME`. Click **Save**.

> **Important:** The specific parameter placeholders, PARAM_USER_ID and PARAM_USER_NAME, are replaced with the actual user identifier and username at runtime only when run as a remediation task through Engage. If you want to use this package outside of Engage, you need to manually provide the actual values for the user identifier and username.

5. Choose this package when you create your remediation task. For more information, see Create remediation task on page 47.

©2026 Tanium Inc. All Rights Reserved

Creating notifications

A notification contains information for users that require only an acknowledgment or dismissal. Notifications are sent to all users of an endpoint and show up on the endpoint as a Tanium End-User Notifications notification message. Unlike a survey that contains multiple questions and is designed to collect feedback from users, a notification is a statement of information.

Use notifications to notify employees of operational and service issues. You can also send notifications to communicate announcements about training, policy updates, and organizational changes. You can send notifications to targeted groups of endpoints and optionally include trigger conditions. You can also include a remediation for each notification. For example, you might create a notification targeted at developers that informs them that your IT organization is aware of an issue with the development software that they use.

Note: These notifications are independent of survey notifications. Surveys include a different type of notification to inform users about the surveys. For more information about survey notifications, see Creating surveys on page 31.

For more information about example scenarios, see Notification examples.

Create a theme

About this task

You can create themes for notifications to customize how they appear to end users. To create and edit themes, you must have a role with the **Engage Themes** Write permission.




1. From the Main menu, go to **Modules** > **Engage > Notification Themes**.
2. Click **Create Theme**.
3. In the **Overview** section, enter a name for the theme and an optional description.
4. If you do not want to use the default content set, select a **Content Set**. Every notification theme requires a content set. If no content set is available, you might need additional permissions. For more information, see Tanium Console User Guide: Role permissions for

©2026 Tanium Inc. All Rights Reserved

content sets.

5. In the **Theme Definition** section, edit any of the following options:

Theme options

Option	Description
Border Color	Select the border color of the notification window. You can choose different colors for light mode and dark mode.
Button Color	Select the color of the acknowledgment button. You can choose different colors for light mode and dark mode.
Left Image	Upload an image that appears on the left side of the window above the notification title, and then add alternative text for accessibility. Figure 3. Left image 
Right Image	Upload an image that appears on the right side of the window above the notification title, and then add alternative text for accessibility. Figure 4. Right image 
Body Image	Upload an image to appear in the body of the notification, select if you want the image to appear to the left or right of the notification text, and then add alternative text for accessibility. Figure 5. Body image 

6. Review the **Theme Preview** section and then click **Submit**.

©2026 Tanium Inc. All Rights Reserved

Result

The new theme is available to use for notifications.

Note: You can edit themes as necessary and delete unused themes. If you edit a theme, the update is applied almost immediately to any currently running or scheduled notifications.

Create notification

1. From the Main menu, go to **Modules** > **Engage > Notifications**.
2. Click **Create Notification** and then select an option from the list.
   - **Blank Notification**: Start with a blank form and complete the fields to build a new notification.
   - **From Template**: Load a notification template that includes predefined trigger conditions, notification settings, and remediation tasks. You can refine the notification properties to suit your needs. The following templates are available by default:

Notification templates

Template name	Use case	Remediation task
AI Tools Policy	Remind your employees to read your corporate AI tools policy.	Link: <Add a related link to your company site>
Clear Microsoft Teams Cache	Improve your employees' Microsoft Teams performance by suggesting them to clear cache on their device.	Task: Clear Microsoft Teams Cache
Compliance Training	Remind your employees to complete time-sensitive tasks, such as corporate compliance training.	Link: <Add a related link to your company site>
Phishing Awareness Reminder	Share security best practices with your employees.	Link: <Add a related link to your company site>
Poor Network Performance [1]	Recommend ways to improve network performance for endpoints with poor network connections.	None

©2026 Tanium Inc. All Rights Reserved

Template name	Use case	Remediation task
Quarterly Expenses Are Due	Remind your employees to submit their quarterly expenses.	Link: <Add a related link to your company site>
Restart Required	Suggest a reboot for endpoints that have not restarted within the last 30 days.	Task: Restart Endpoint
Zoom Outage	Notify employees of service disruptions, such as Zoom outages.	None

[1] Requires the Tanium Performance solution.

3. Enter a title and optional description. The title appears to the user in the notification on the endpoint.
4. If you do not want to use the default content set, select a **Content Set**. Every notification requires a content set. If no content set is available, you might need additional permissions. For more information, see Tanium Console User Guide: Role permissions for content sets.
5. (Optional) Define one or more trigger conditions. A trigger condition defines when the end user of the endpoint receives the notification. The trigger condition can be based on a Tanium sensor. If you do not define trigger conditions, the notification is sent to end users on all targeted endpoints; you define targets when you send the notification.
    a. Click **Add Condition**, then click **+ Row** or **+ Group** to define the trigger condition.
    b. Click **Apply** ✓ to save the condition, then click **Save**.
    c. In **Minimum time between notifications**, specify the amount of time between notifications that the user receives on the endpoint. Enter a value from 1 hour to 24,855 days, in hours or days. By default, this value is 1 day. Endpoints must still match any trigger conditions to receive the notification.
6. Configure the notification.
    - Select the **Original Language** of the notification. You can provide translations in the **Multi-Language Support** section.
    - (Optional) Select a **Theme**. Themes apply to both toast and modal notifications. To create additional themes, see Create a theme on page 63.
    - Select if you want the notification to appear in the lower right corner of the screen as

©2026 Tanium Inc. All Rights Reserved

a **Toast** or to take focus as a **Modal**.

- Enter and format the **Notification Text**.
- Enter the **Button Text**.
- Select a **Remediation**.
    - Select **None** if no remediation is necessary.
    - Select **Link** to include a link for the user. For example, you can include a link to open a ticket with the IT help desk. The link must start with `https://`.
    - Select **Task** to deploy a task to the endpoint when the user clicks the button. You can choose from the following predefined tasks in addition to any custom tasks defined in your environment:

      Restart Endpoint
      : Restarts the target device.

      Clear Microsoft Teams Cache
      : Clears cache to resolve problems with Microsoft Teams.

      Clear DNS Cache
      : Clears DNS cache to help resolve network issues.

      Enable / Disable Fast Start
      : Enables or disables the Windows OS Fast Start feature.

      Restart <application>
      : Restarts the (macOS) Apple Safari, Cisco Webex, Google Chrome, Microsoft Edge, Microsoft Outlook, Microsoft Teams, Mozilla Firefox, Slack, or Zoom application.

      User Disk Cleanup
      : Performs light (Recycle bin empty) clean.

- Preview the notification. The notification appears in dark mode or light mode based on endpoint settings.

7. (Optional) Add multi-language support. Click **Add Languages**, select one or more languages,

©2026 Tanium Inc. All Rights Reserved

expand each language you selected, and enter the translated text. The default notification language is based on the locale and OS of the user.

Tip: The **Add Languages** option is disabled until you add the **Notification Title** and **Notification Text**.

8. Save the notification. You can either save the notification as a draft or save and schedule the notification to run.

Schedule notification run

About this task

When you create a notification, the notification is in draft mode until you schedule it to run. When a notification runs, the notification is sent to the targeted endpoints and appears to endpoint users when trigger conditions are met. If the notification does not contain any trigger conditions, the notification appears to all end users on targeted endpoints.

1. From the Main menu, go to **Modules** > **Engage > Notifications**.
2. Click the name of the notification that you want to schedule.
    a. If the notification has a **Draft** status, click **Save and Schedule** to edit the schedule.
    b. If the notification has a **Done** status, you must clone the notification to rerun it. For more information, see Clone notification on page 69.
    c. If the notification has a **Scheduled** or **Running** status, click **End Notification** and then clone the notification. For more information, see Clone notification on page 69.
3. Set a **Start Time** and **End Time**. The **End Time** includes the following options:
    a. **Scheduled**: Set a date and time for the notification to stop running.
    b. **None**: Do not set an end time and let the notification run indefinitely.
    You can also choose to use UTC (default) or the endpoint local time to schedule the survey.
4. Select one or more computer groups to target with the notification. Only endpoints in the computer groups are eligible to receive the notification. The user that creates the notification must have management rights to this computer group. To assign computer groups to a user, see Tanium Platform User Guide: Manage computer group assignments for a user.
5. Click **Run Notification**.

©2026 Tanium Inc. All Rights Reserved

Result

The notification runs according to the criteria that you select. To end a running notification, open the notification from the **Notifications** page and click **End Notification**.

Clone notification

About this task

Clone an existing notification to create similar notifications or to run a notification again. You can clone notifications that are in the **Running** or **Done** state.

1. From the Main menu, go to **Modules** > **Engage > Notifications**.
2. Select the notification that you want to clone by using one of the following methods:
   - Click the name of the notification. The **Notification Details** page appears.
   - Select the checkbox for the notification. The Clone icon appears in the **Notifications** grid header.
3. Click Clone and then edit the notification details.
4. Save the notification. You can either click **Save as Draft** or **Save and Schedule**.

View existing notification status

You can view the latest notifications on the **Engage Overview** page. To view all notifications, from the Engage menu, go to **Notifications**.

Notification status icons

Status	Description
	The notification is in draft mode. Finish editing and schedule the notification run.
	The notification is currently running against targeted endpoints.
	The notification is scheduled to run at a future date and time.

©2026 Tanium Inc. All Rights Reserved

Status	Description
	The notification is done.
	An error occurred when scheduling or sending the notification.

Delete notification

About this task

You can delete notifications that are in the **Draft**, **Done**, or **Error** state.

Tip: To end a running or scheduled notification, open the notification from the **Notifications** page and click **End Notification**.

1. From the Main menu, go to **Modules** > **Engage > Notifications**.
2. Click the name of the notification that you want to delete.
3. Click Delete .

Result

Engage deletes the notification and returns to the **Notifications** page.

Export and import notifications

You can export notifications from one environment and import them to another environment. For example, export notifications from a test environment and import them to a production environment.

Export notification

1. From the Main menu, go to **Modules** > **Engage > Notifications**.

©2026 Tanium Inc. All Rights Reserved

2. To export all notifications, click **Export All**.

   Tip:

   To export a subset of notifications, select one or more notifications and then click **Export**. You can also export an individual notification by clicking **Export** in the View Details panel.

Result

A JSON file downloads to the browser download folder.

Import notification

1. From the Main menu, go to **Modules** > **Engage > Notifications**.
2. To import previously exported notifications, click **Import** and then provide the previously downloaded JSON file.

Result

If you import a notification that has the same name as an existing notification, Engage appends **[<#>]** to the name of the imported notification. For example, if **Notification_Name** already exists, then Engage imports it as **Notification_Name [1]**.

©2026 Tanium Inc. All Rights Reserved

Troubleshooting Engage

If Engage is not performing as expected, you might need to troubleshoot issues or change settings.

Collect logs

Collect troubleshooting package for Engage

About this task

The information is saved as a ZIP file that you can download with your browser.

1. From the **Engage Home** page, click Help ?, then the **Troubleshooting** tab.
2. Click **Download Support Bundle**. A tanium-Engage-support.[number].zip file downloads to the local download directory.
3. Contact Tanium Support to determine the best option to send the ZIP file. For more information, see Contact Tanium Support on page 74.

Collect troubleshooting information from endpoints

About this task

You can use Client Management to directly connect to an endpoint and collect a bundle of logs and other artifacts, sometimes referred to as an *Endpoint Must Gather* (EMG).

1. From the Main menu, go to **Shared Services** > **Client Management**.
2. From the Client Management menu, click **Client Health**.
3. In the **Single Endpoint View** search box, enter all or part of an IP address or a computer name.
   Matching results appear after the search completes.
4. From the search results, click the computer name.
   Client Management opens the Endpoint Details page in Single Endpoint View (SEV).

©2026 Tanium Inc. All Rights Reserved

5. Click the **Client Health** tab and, if the endpoint is not yet **Connected**, click **Direct Connect**.
6. In the **Available Steps** grid, select the domains (types of logs and artifacts) for which you want to gather troubleshooting information.
   For Patch information, select the **Core** and **Patch** domains.

   For Comply information, select the **Comply** domain and then select **Comply Database**, **Comply Extension Data**, and **Comply Intel**.

   For Endpoint Management for Operational Technology entity provider information, select the **Core** domain and then select **Tanium Client Logs**. Select the **Entity** domain and then select **Config Data**, **Entity Log**, and **Entity Provider Metadata**.
7. Click **Gather from Endpoint**.
   The selected logs and artifacts are gathered from the endpoint. The package appears in the **Must Gathers** section, and the name of the package corresponds with its time stamp.
8. When **Finished** appears in the **Run State** column, select the package and click **Download** to download a ZIP file that contains the troubleshooting information.
   For more information about collecting troubleshooting information in Single Endpoint View, see Tanium Reporting User Guide: Collect troubleshooting information.

   For more information about how to connect directly to endpoints, see Tanium Direct Connect User Guide.

   For more information about Client health features in Client Management, see Tanium Client Management User Guide: Monitor the Client health overview in Client Management and Tanium Client Management User Guide: Access detailed Client health and troubleshooting information on an endpoint.

Verify endpoint tools

If you are experiencing issues such as a feature not working on an endpoint or seeing incorrect data in the workbench, confirm that your endpoints have the latest toolset version.

For more information, see Tanium Endpoint Configuration User Guide: Identify and resolve issues with endpoint tools or Client Extensions and Reference: Client extensions and endpoint tools used for Tanium solutions.

©2026 Tanium Inc. All Rights Reserved

Contact Tanium Support

To contact Tanium Support for help, sign in to the Tanium Customer Community.

For more information about submitting a support case, see Case Submission Form.

©2026 Tanium Inc. All Rights Reserved